



GROUND DRIVE
MANURE
SPREADERS



STRONG | EFFICIENT | RELIABLE

HSMFGCO.COM

S1200 SERIES

GROUND DR



MODEL S1225



FEATURES

- **Powdercoat painted** for durability and performance.
- **Polybonded floor** minimizes main apron drag.



EASY OPERATION

Features simple lever to engage/disengage the apron and beater.(S1250 and S1280 Shown)
Easy access to apron tension bolts for adjustment.

ES RIVE



MODEL S1250



REAR PAN OPTION

An optional rear pan is available on all S1200 series Ground Drive models.



DESIGNED FOR PERFORMANCE

Reliable chain driven beater. The main apron is driven by a simple adjustable ratchet drive mechanism.



S1225

The 20" diameter, 8-paddle beater provides an even spread of material.

6x12 deep lug traction tires for performance are standard.

Separate apron engage/disengage lever and beater engage/disengage lever.



S1250 & S1280

The S1250 features an 8-paddle beater, and the S1280 utilizes a 10-paddle, heavy-duty beater assembly.

Both also feature 7.6x15 deep lug tires.



MODEL S1280



	S1225	S1250	S1280
Capacity cu. ft. struck level*	11.22	31.27	41.69
Capacity cu. ft. heaped*	14.27	48.67	71.04
Top of flare width	28-1/2"	39"	51"
Inside width	22"	36"	48"
Inside length	6'	7' 1"	7' 1"
Inside depth	17"	17-1/2"	17-1/2"
Overall length	9' 1"	13' 4"	13' 4"
Overall loading height - top of flare	30"	33"	33"
Overall width w/standard tires	42"	58"	72"
Spindle size	1-1/4"	1-3/4"	2"
Diameter of beater	20"	17-1/2"	18-1/2"
Number of paddles	8	8	10
Main apron chain	55	62	67H
Box construction	Powdercoat painted steel		
Floor construction	Polybonded		
Apron drive	Adjustable ratchet drive		
Upper beater	N/A		
Swing away jack	N/A	Standard	Standard
Weight w/tires	350 Lbs.	790 Lbs.	975 Lbs.

*per ASAE S324.2



PROUDLY BUILT IN MARSHFIELD, WISCONSIN :: HSMFGCO.COM

