



TOP SHOT
**MANURE
SPREADERS**



STRONG | EFFICIENT | RELIABLE

HSMFGCO.COM



MODEL TS5226



MODEL TS5234

TS5200 SERIES

TOP SHOT



SUPERIOR SPREAD PATTERN

The heavy-duty expeller system, with a quick release poly lined fine spread pan and side fins, helps cut the drift of material towards the tractor and spreader to provide an excellent spread pattern.



REDUCE MATERIAL BRIDGING

The auger system hydraulically raises and lowers a full 8" to break-up material that may bridge during unloading. The left side poly liner allows material to slide to the auger.



AUGER CYLINDER SYSTEM

Cylinder system raises and lowers the main auger evenly to keep material moving to the expeller.



REVERSIBLE SQUARE TOOTH PADDLES

Reversible bolt-on square tooth paddles shred and rip material with a Top Shot action for an even spread pattern.



AUTOMATIC OILER SYSTEM

An automatic oiler system oils the drive system chains anytime the discharge door is raised. (optional on TS5215)



SET DISCHARGE DISTANCE

A manual adjust top shield allows you to set the distance of material being discharged. A hydraulic deflector is also available and comes standard on the TS5234 & TS5242.

TS5215

TOP SHOT



MODEL TS5215

FEATURES

- 30" wide *TOP SHOT* expeller beater
- Adjustable hitch
- Scraper holder
- Left side poly lined tank
- Remote grease system
- Jack storage on left side of manure spreader
- 24-inch diameter round core auger



REAR SPLASH GUARD

Optional rear splash guard and side rails.



AUGER SYSTEM

Feature a 24-inch diameter round core segmented auger.



TS5215



SPROCKET REDUCTION SYSTEM

The drive system features a sprocket reduction system with heavy-duty chain and an overrunning torque limiting clutch for protection and smooth power transfer.



CHOICE OF AXLES

Choice of standard or drop tandem axles
Tandem axle is available with your choice of 295R x 22.5 recap tires, 16.5 x 16.1 flotation tires or 19L x 16.1-10 tires.



POLY-LINED FINE SPREAD PAN

Features a 3-section 30" expeller with a quick release poly-lined fine spread pan.

OTHER OPTIONS

- 1000 RPM 1-3/8" PTO
- Rear splash guard w/side rails
- Rear splash guard
- Automatic oiler for roller chains
- Highway lighting kit

TS5220/TS5226/TS5234/TS5242

TOP SHOT



MODEL TS5220

FEATURES

- 40" wide *TOP SHOT* expeller beater
- Adjustable hitch
- Scraper holder
- Left side poly lined tank
- Highway lighting system
- Automatic chain oiler system
- Remote grease system
- Jack storage on left side of manure spreader
- 24-inch (TS5220, TS5226) or 30-inch (TS5234, TS5242) diameter round core auger
- Shear-bolt drive line protection on TS5220 and TS5226



HYDRAULIC LID & REMOTE

The optional hydraulic lid opens and latches from either side, requiring a third tractor remote. An electrical toggle switch locks and unlocks the lid. (TS5234, TS5242)



AUGER CYLINDER SYSTEM

A master/slave cylinder system raises and lowers the main auger evenly to keep material moving to the expeller.



HYDRAULIC FEATURES

The standard hydraulic adjust top expeller deflector sets the distance of the spread pattern, while the hydraulic door cylinder allows adjustment for rate of application. (TS5234, TS5242)



HEAVY-DUTY GEARBOX

The drive system features a heavy-duty gearbox reduction with an overrunning torque limiting clutch for protection and smooth power transfer. (TS5234, TS5242)



ELECTRIC VALVE

Optional electric valve for use with hydraulic deflector to be able to run on tractors with only 2 SCVs. (TS5220 and TS5226, requires optional hydraulic deflector.)

OTHER OPTIONS

1000 RPM 1-3/8" PTO (TS5220), 540 RPM PTO (TS5226)
1000 RPM 1-3/4" PTO (TS5234, TS5242)
2-Wheel electric over hydraulic disc brakes on rear wheels (TS5234, TS5242)
High Axle or Drop Axle (TS5220), Heavier tandem axle (TS5226, TS5234)
Discharge deflector hydraulic cylinder w/hoses (TS5220, TS5226)
Discharge deflector cylinder electric valve
Hydraulic opening lid (TS5234, TS5242)
Clevis, pintle or bullnose hitch (TS5220 - TS5242)
Digi-Star™ GT400 or Nutrient Tracker Scale System with GPS



	TS5215	TS5220	TS5226	TS5234	TS5242
Cu. ft. struck level	172	268.6	347	451	564
Gallon capacity	1,286 / 1,500 w/extension	2,009	2,596	3,377	4,200
Tank length	14'	16'	16'	16'	20'
Overall length	20' 10"	22' 8"	22' 8"	23' 7"	27' 7"
Tank width - top	70"	76"	87"	97"	97"
Auger diameter	24"	24"	24"	30"	30"
Poly lined tank	Left side				
PTO overrunning clutch	Standard				
Driveline protection	Torque limiting clutch & shear bolts			Torque limiting clutch	
PTO choices	540 RPM Std. / 1000 RPM Opt.		1000 RPM Std. / 540 RPM Opt.	1-3/8" or 1-3/4" 1000 RPM	
Expeller width	30"	40"			
Front splash guards	Standard				
Rear splash guards	Optional	Standard			
Automatic oiler	Optional	Standard			
Highway lighting	Optional	Standard			
Weight	5,740 Lbs.	6,860 Lbs.	7,880 Lbs.	10,940 Lbs.	16,500 Lbs.
Standard hubs	8 Bolt / 8,000 Lb.			10 Bolt / 12,000 Lb.	10 Bolt / 25,000 Lb.
Standard Safety Chain	30,000 Lb.		40,000 Lb.	60,000 Lb.	



PROUDLY BUILT IN MARSHFIELD, WISCONSIN :: HSMFGCO.COM

