



STANDARD DUTY PTO
MANURE
SPREADERS



STRONG | EFFICIENT | RELIABLE

HSMFGCO.COM

S2200 SERIES

STANDARD DUTY



MODEL S2280



MODEL S2213



APRON SPEEDS

A patented, heavy-duty enclosed two-speed gearbox plus a beater shut-off allows you to choose your unload rate.



S2213 & S2217

The large diameter beater on the S2213 and S2217 models ensures aggressive shredding action with wide, even spread patterns.



MODEL S2217

FEATURES

- The S2200 series models feature durable **powdercoated paint**.
- The S2200 series use an all-welded heavy-duty A-frame hitch assembly this is built to withstand the stress of heavy loads and rough roads.
- All spreaders utilize a **polybonded floor** to minimize main apron drag, reducing the power needed to move the load.
- 10,100# safety chain
- Each model is equipped with standard tires and silver rims:
 - S2280 6.7X15
 - S2213 240/80R15
 - S2217 295/75R22.5



REAR PAN OPTION

An optional rear pan is available for all models.



MAIN APRON TIGHTENER BOLTS

On all models, the main apron tensioner bolts are located outside on the lower right and left corners of the main frame for adjustment.



2-SPEED APRON CONTROL

The front control panel for the 2-speed apron drive system allows you to select and see what gear you are in.

OTHER OPTIONS

- | |
|-------------------------------------|
| Top Beater (S2213 and S2217) |
| Hydraulic endgate (S2213 and S2217) |

BUILT TOUGH. BUILT TO LAST.



| | S2280 | S2213 | S2217 |
|--------------------------------------|--------------------------|--------------|--------------|
| Capacity cu. ft. struck level* | 45.11 | 67.61 | 91.63 |
| Capacity cu. ft. heaped* | 74.18 | 110.67 | 152.13 |
| Top of flare width | 51" | 63-1/2" | 63-1/2" |
| Inside width | 48" | 54" | 54" |
| Inside length | 7' 4" | 7' 4" | 11' 1" |
| Inside depth | 19-3/4" | 25-3/4" | 25-3/4" |
| Overall length | 13' 10" | 14' 7" | 17' 8" |
| Overall loading height - top of side | 35" | 47" | 47" |
| Overall height w/hydraulic endgate | N/A | 51" | 49" |
| Overall width w/standard tires | 76" | 82-3/4" | 87" |
| Spindle size | 2" | 2" | 2" |
| Diameter of beater | 18-1/2" | 27" | 27" |
| Number of paddles | 10 | 8 | 8 |
| Main apron chain | 67H | T-Rod | T-Rod |
| Box construction | Powdercoat painted steel | | |
| Floor construction | Polybonded | | |
| Apron drive | Gearbox, 2-speed PTO | | |
| Upper beater | N/A | Optional | |
| Swing away jack | Standard | | |
| Weight w/tires | 1,140 Lbs. | 1,600 Lbs. | 2,030 Lbs. |

*per ASAE S324.2



PROUDLY BUILT IN MARSHFIELD, WISCONSIN :: HSMFGCO.COM

