



**GM9117 AND RM7117**

# **GRINDER MIXER & ROLLER MIXER**



---

**STRONG | EFFICIENT | RELIABLE**

---

[HSMFGCO.COM](http://HSMFGCO.COM)

# GM9117

## GRINDER MIXER



### GM9117 & RM7177 DISCHA

8" Unloading auger tube dia
12' Unloading auger length
240 Degree unloading auger
19' at 53 degrees standard u
21' 6" at 53 degrees unloadi extension
23' 10" at 53 degrees unload extension
Adjustable auger rest

FEATURES	OPTIONS	HAMMER MILL
167 Cu. Ft./135 bushel capacity	Rear supplement hopper	21" wide
21" mill with 66 hammers	1000 RPM PTO	20" cylinder diameter
Self-contained hydraulic system with 15 gallon reservoir and filter	Corn Cob style or Conventional variable speed swinging intake augers	8 'A' section banded v-belt grinder drive
Shear bolt protection on the mixing auger and transfer auger drive	3' or 6' folding extension	66 - 4 way reversible grinder hammers
8-section banded main drive belt	Multiple mill screen size options	2700 RPM cylinder speed
Two heavy duty 3" x 17" magnets remove any metal that may accidentally mix with the material entering the mill	2500 or 3410 Digi-Star scale	600 Square inch grinder screen area
240-degree swing 12' discharge auger with two tractor remotes to control swing and raise/lower		

# RM7117

## ROLLER MIXER

### LONG AUGER

Auger diameter

Auger rotation

Unloading auger reach

Mixing auger reach w/3'

Discharge auger reach w/6'



### FEATURES

### OPTIONS

### ROLLER MILL

167 Cu. Ft./135 bushel capacity

8' Conventional swinging intake auger

18" wide

14" mixing auger with 30" base

Rear supplement hopper

16" diameter chill cast rolls (2)

Self-contained hydraulic system with 15 gallon reservoir and filter

3' or 6' folding extension

Direct roller drive

Shear bolt protection on the mixing auger and transfer auger drive

2500 or 3410 Digi-Star scale

Leaf spring roll protection

Top hopper with magnet

4,5,8,10,12 or 15 GPI Rolls

Standard 6 GPI Rolls

240-degree swing 12' discharge auger with two tractor remotes to control swing and raise/lower



<b>GM9117 AND RM7117</b>	
Tank capacity	135 Bushel / 167 Cu. Ft.
Tank diameter	74"
Diameter of mixing auger	14" diameter w/30"base
Ladder	Foldable, rear mount, non-slip
Tank windows	5-port hole style
Overall height	10' 8 "
Overall width	8' 6" w/o infeed auger option
Overall length	15'
Ground clearance	12"
Supplement hopper	Side mount / Optional Rear Supplement Hopper
Feeder	Gravity hopper
PTO drive	GM9117 540 RPM / Optional 1000 RPM RM7117 540 RPM
Drive line protection	Shear bolt on mixing auger and transfer auger drive
Horsepower requirements	540 RPM up to 115HP / 1000 RPM up to 145HP
Tires	320/70R15
Transport lighting	Standard
Jack	Standard
Scale system	Weight bars/spindles (Monitor is optional)
Drive system	Self-contained hydraulic system
Pump pressure	3,200 PSI maximum
Oil Flow	12 GPM

