



TR / RR / RT
TEDDERS
and RAKES



STRONG | EFFICIENT | RELIABLE

HSMFGCO.COM

TEDDERS AND RAKES

ROTARY AND IN-LINE



RT-5800-H



RT5200H / RT5800H TEDDERS

- The outer mounted rotars automatically follow uneven terrain.
- The rotars are driven by the universal joint. This system is a press-forged steel double universal joint.
- The outer rotars are folded hydraulically from a set of tractor remotes.



RTG2 TEDDER

- 12 flexible steel teeth.
- Oil bath gearbox
- Cardan shaft with slip clutch.



RTG6 TEDDER

- 16 flexible steel teeth.
- Central tandem wheels adapt to any type of terrain.
- Grease lubricated system.
- 540 RPM.
- Heavy-duty shielded PTO shaft with clutch protection.



TR-9-3W

TR RAKE MODELS

All models feature independent rake wheel spring suspension. Rake wheels are lowered, and raised into transport position by the hydraulic cylinder that is operated from the tractor remote.



RR420 RAKE

- Constant velocity PTO with slip clutch.
- Adjustable front cylinder.
- Sealed oil bath gearbox.
- Hydraulic lift cylinder.
- Tandem axle walking beam.
- Easy ground-height adjustment.
- Quick remove tine arms.



TR-9 & TR-9-3W RAKES

Rakes feature a spring loaded pin to select up to 4 pole adjustments. This along with the many possible wheel settings, gives a wide range of working widths.



TR-9/S RAKE

- Narrow transport width of 77".
- Strong joint system moves from transport to working position through hydraulic cylinders operated by the tractor remote lever.
- Hydraulic cylinder/joint system allows the operator to make width adjustments on the go, adapting to any changing field conditions.



ROTARY TEDDERS	RTG2	RTG6	RT-5200-H	RT-5800-H
Working width	10' 2"	24'	17'	19'
Transport width	8' 2"	9' 8"	10' 3"	11'
Weight	419 Lbs.	1917 Lbs.	1000 Lbs.	1225 Lbs.
Tires	5 x 600-6	16 x 6.50-8		

ROTARY RAKE	RR420
Number of arms	11
Number of double tines per arm	4
Working width	13' 8"
Gearbox	Sealed in Oil Bath
Rotar diameter (working width)	11' 2"
Transport width	5' 9"
Tires	18/8.5 x 8
Weight	1369 Lbs.

TRAILER MODEL IN-LINE RAKES	TR-9	TR-9-3W	TR-9/S
Number of rake wheels	9		
Wheel diameter	55"		
Tines per wheel	40		
Rake wheel tine diameter	7 mm		
Number of tires	2	3	

